



Conseal Type CSA: Standard Flexible Conduit

Trade Size	Item ID	Std. Pkg. METERS	Inside Diameter Min	Outside Diameter		Bend Diameter	Weight Kg/m (lbs/cft)
				Min	Max		
3/8" (12)	10041	30	12.29 (0.484)	17.50 (0.690)	18.00 (0.710)	102 (4.0)	0.35 (24)
	10044	300					
1/2" (16)	10061	30	15.80 (0.622)	20.80 (0.820)	21.30 (0.840)	152 (6.0)	0.42 (28)
	10063	150					
	10064	300					
3/4" (21)	10071	30	20.83 (0.820)	26.16 (1.030)	26.67 (1.050)	203 (8.0)	0.55 (37)
	10073	150					
	10074	300					
1" (27)	10081	30	26.44 (1.041)	32.80 (1.290)	33.40 (1.315)	254 (10.0)	0.80 (54)
	10083	150					
1-1/4" (35)	10090	15	35.05 (1.380)	41.40 (1.630)	42.20 (1.660)	318 (12.5)	1.13 (76)
	10091	75					
1-1/2" (41)	10100	15	40.01 (1.575)	47.40 (1.865)	48.30 (1.900)	381 (15.0)	1.45 (97)
	10101	45					
2" (53)	10111	15	51.31 (2.020)	59.40 (2.340)	60.30 (2.375)	508 (20.0)	1.67 (112)
	10113	30					
2-1/2" (63)	34075	8	62.99 (2.480)	72.10 (2.840)	73.00 (2.875)	635 (25.0)	2.88 (194)
3" (78)	34085	8	77.98 (3.070)	87.90 (3.460)	88.90 (3.500)	762 (30.0)	4.00 (269)
4" (103)	34095	8	101.60 (4.000)	113.30 (4.460)	114.30 (4.500)	1016 (40.0)	6.00 (403)

All dimensions in mm (inches)



Modified S Profile with cord packing 3/8" thru

Square Lock Profile with cord packing 1-1/4" thru 2"

Interlocked Profile 2-1/2" thru 4"

Conseal Type CSA:



- Flexible metal core liquid-tight conduit.
- Suitable for use in hazardous locations per CEC: Class I, Zone 2 & Div. 2; Class II Div. 1 & 2; Class III Div. 1 & 2.
- Also available by special order in other colours. (consult factory)
- Sequentially meter marked for easy cutting and stock control.
- Uses standard liquid-tight connectors for easy installation.
- Available in custom cut lengths

For connectors for this conduit, see page 19-20
 For cutting instructions, see page 37
 For Chemical Resistance, see page 38

SPECIFICATIONS:

- Galvanized steel core with Liquid-tight PVC jacket
- Colour: Black
- Temp. range: -20°C to +75°C (-4°F to +167° F)
- FT-4 Rated
- UV (sunlight) Resistant
- Corrosion Resistant
- Sequentially meter marked
- CSA Approved # 17419

APPLICATIONS:

- Standard industrial and commercial applications
- Motor hookup