



Firetech: Protective Sleeving

Firetech Sleeve/Wrap/Tape/Blanket:

- Flexible Sleeving for protection of cables from high heat or flame.
- Silicone based cover over a knitted glass fiber sleeve.
- Superior temperature range for extreme environments.
- Abrasion resistant—Ready for the worst environment.
- The ultimate protection for harsh industrial applications.
- Can be enhanced by adding additional layer of Firetech Lite.
- Sleeve is UL Recognized for Canada and US.



Firetech VCO:

- Any of the standard Firetech Sleeves can be slit and sewn with a high temperature hook-and-loop closure. This allows easy assembly and removal without disconnecting cables.
- Ordered by required length. Consult Factory for details.



Firetech Lite:

- Flexible Sleeving for protection of cables from high heat.
- Braided glass fiber sleeve.
- Superior temperature range for extreme environments.
- Can be used to increase heat resistance of Firetech Sleeve.



Firetech Connectors:

- Anamet Stainless Steel fittings for Firetech come with a special internal collar to allow the Firetech Sleeve to be held firmly, creating a method of sealing the ends of the sleeve that is stronger than Tape. Allows interconnect into standard NPT applications and provides a cleaner finished installation.



Firetech SLEEVE



The following part numbers are available in non-standard lengths as required:

FTS-4 (1/4")
 FTS-6 (3/8")
 FTS-8 (1/2")
 FTS-12 (3/4")
 FTS-16 (1")

Change part number to:
 FTS-x-9

Description	Inside Diameter	Weight Kg(lb)	Std. Pkg.
	Inches (mm)	per package	FEET
FTS-4-5	1/4" (6)	1.60 (3.53)	50
FTS-5-5	5/16" (8)	1.80 (3.97)	50
FTS-6-5	3/8" (10)	2.25 (4.96)	50
FTS-7-5	7/16" (11)	2.50 (5.51)	50
FTS-8-5	1/2" (13)	2.95 (6.50)	50
FTS-10-5	5/8" (16)	3.20 (7.05)	50
FTS-12-5	3/4" (19)	3.85 (8.49)	50
FTS-14-5	7/8" (22)	4.10 (9.04)	50
FTS-16-5	1" (25)	4.75 (10.47)	50
FTS-18-5	1-1/8" (29)	5.00 (11.02)	50
FTS-20-5	1-1/4" (32)	5.90 (13.01)	50
FTS-22-5	1-3/8" (35)	6.80 (14.99)	50
FTS-24-5	1-1/2" (38)	7.75 (17.09)	50
FTS-26-5	1-5/8" (41)	7.95 (17.53)	50
FTS-28-5	1-3/4" (44)	8.20 (18.08)	50
FTS-32-5	2" (51)	9.10 (20.06)	50
FTS-36-5	2-1/4" (57)	9.75 (21.49)	50
FTS-40-5	2-1/2" (64)	10.45 (23.04)	50
FTS-44-5	2-3/4" (70)	11.60 (25.57)	50
FTS-48-5	3" (76)	13.20 (29.10)	50
FTS-52-5	3-1/4" (83)	15.70 (34.61)	50
FTS-56-5	3-1/2" (89)	16.35 (36.05)	50
FTS-60-5	3-3/4" (95)	16.80 (37.04)	50
FTS-64-5	4" (102)	17.50 (38.58)	50
FTS-72-5	4-1/2" (114)	18.40 (40.56)	50
FTS-80-5	5" (127)	19.20 (42.33)	50

SPECIFICATIONS:

- Knitted glass fiber coated with silicone rubber (non-asbestos)
- Colour: Red
- Temperature range:
 +260°C (500°F) Continuous
 +1090°C (2000°F) 15-20 min.
 +1650°C (3000°F) 15-30 sec.
- Firetech Tape rated 246°C (475°F)
- Silicone cover sheds molten metal/glass immediately avoiding heat transfer
- UL Recognized for Canada and US—File # E321462 (Sleeve only)

APPLICATIONS:

- Extreme duty applications
- Extreme high heat or flame

All dimensions inches(mm)

Firetech WRAP



Description	Width	Weight Kg(lb)	Std. Pkg.
	Inches (mm)	per package	FEET
FTW-1-5	1" (25)	1.35 (2.98)	50
FTW-2-5	2" (51)	2.25 (4.96)	50
FTW-3-5	3" (76)	3.65 (8.05)	50
FTW-4-5	4" (102)	4.75 (10.47)	50
FTW-5-5	5" (127)	5.90 (13.01)	50

TAPE



Description	W x L x Thickness	Weight Kg(lb)	Std. Pkg.
	Inches (metric)	per roll	
FTT-16	1" x 432" x .020" (25.4mm x 10.9m x 0.51mm)	0.14 (0.31)	Per Roll
FTT-24	1 1/2" x 432" x .060" (38.1mm x 10.9m x 1.52mm)	0.45 (0.99)	Per Roll

BLANKET



Description	Width inches (mm)	Weight Kg(lb)	Std. Pkg.
	& Sides Coated	per foot	
FSH-36-2	36" (914mm) FSH-36-2 coated 2 sides	0.36 (0.79)	Per Foot
FSH-60-2	60" (1,524mm) FSH-60-2 coated 2 sides	0.91 (2.01)	Per Foot
FSH-40-1	40" (1,014mm) FSH-40-1 coated 1 side	0.60 (1.32)	Per Foot

Phone: (613) 398-1313
 Fax: (613) 398-6262
 www.anametcanada.com
 E-mail: csr@anametcanada.com

Anamet Canada Inc.
 PO Box 240, 36 Wolfe St.
 Frankford, Ontario K0K 2C0



Firetech Lite: Extreme Temperature Sleeve

Firetech Lite:



Description	Inside Diameter	Weight Kg(lb)	Std. Pkg.
	Inches(mm)	per package	FEET (M)
FTL-8-5	1/2" (13)	2.95 (6.50)	330 (101)
FTL-12-5	3/4" (19)	3.85 (8.49)	300 (91)
FTL-16-5	1" (25)	4.75 (10.47)	290 (88)
FTL-20-5	1-1/4" (32)	5.90 (13.01)	280 (85)
FTL-24-5	1-1/2" (38)	7.75 (17.09)	225 (69)
FTL-32-5	2" (51)	9.10 (20.06)	190 (58)
FTL-40-5	2-1/2" (64)	10.45 (23.03)	180 (55)
FTL-48-5	3" (76)	13.20 (29.10)	170 (52)
FTL-64-5	4" (102)	17.50 (38.58)	140 (43)

All dimensions in mm (inches)

SPECIFICATIONS:

- Braided glass fibre sleeve
- Colour: White
- Temperature range:
+538°C (1000°F) Continuous
+705°C (1300°F) 15-20 min.
- Provides economical cable protection where exposure to molten splash, oils or moisture is not a factor.
- Can be used in conjunction with Firetech Sleeve to provide additional insulation values.

APPLICATIONS:

- High heat areas where splash and oils are not a factor.

SSFT Series Liquid-tight Connectors:

Straight:



FTS/FTL Size	Item ID	Dimensions			KO Size NPT	Weight Kg(lb)/Pkg	Standard Package
		A	B	C			
1/2"	SSFT38	37.00 (1.457)	13.00 (0.512)	26.00 (1.024)	1/2"	1.6 (3.5)	25
5/8"	SSFT50	37.00 (1.457)	13.00 (0.512)	29.00 (1.142)	1/2"	2.0 (4.4)	25
7/8"	SSFT75	40.00 (1.575)	15.00 (0.591)	35.00 (1.379)	3/4"	1.1 (2.4)	10
1"	SSFT100	46.00 (1.811)	15.00 (0.591)	45.00 (1.772)	1"	0.7 (1.4)	5

All dimensions in mm

90 Degree:



FTS/FTL Size	Item ID	Dimensions				KO Size NPT	Weight Kg(lb)/Pkg	Standard Package
		A	B	C	D			
1/2"	SSFT9038	36.00 (1.417)	13.00 (0.512)	26.00 (1.024)	43.00 (1.693)	1/2"	1.0 (2.2)	10
5/8"	SSFT9050	36.00 (1.417)	13.00 (0.512)	29.00 (1.142)	43.00 (1.693)	1/2"	1.3 (2.9)	10
7/8"	SSFT9075	43.00 (1.693)	15.00 (0.591)	35.00 (1.379)	48.00 (1.890)	3/4"	1.6 (3.5)	10
1"	SSFT90100	48.00 (1.890)	15.00 (0.591)	45.00 (1.772)	59.00 (2.323)	1"	1.2 (2.6)	5

All dimensions in mm