

























Table of Contents:

	Designation	Page	Product Features	Size Range	Approval
Metallic Liquid-tight	CSA	4	Conseal: Standard metallic liquid-tight - BLACK 75°C	3/8" - 4"	
	CW-BLUE	5	Conseal: Computer grade metallic liquid-tight - BLUE 75°C	3/8" - 2"	
	EFST	6	Sealtite: Extra-flexible metallic liquid-tight - GREY 60°C	1/4" - 6"	
	UA-CSA	7	Sealtite: Dual listed metallic liquid-tight - GREY 60°C	3/8" - 4"	 
	OR	8	Sealtite: Oil Resistant metallic liquid-tight - GREY 105°C	3/8" - 2"	
	MTC	9	Sealtite: Machine tool metallic liquid-tight - BLACK 60°C	3/8" - 2"	
	HTC	10	Sealtite: High temperature metallic liquid-tight - BLACK 105°C	3/8" - 2"	
	HC	11	Sealtite: High temperature metallic liquid-tight - GREY 105°C	3/8" - 2"	
	HTUA	12	Sealtite: High temperature UL metallic liquid-tight - GREY 105°C	3/8" - 4"	 
	HTX	13	Conseal: Extreme temperature metallic liquid-tight - YELLOW 135°C	3/8" - 2"	
	HCX	14	Sealtite: Extreme temperature metallic liquid-tight - BLACK 150°C	3/8" - 2"	
	EFL	15	Sealtite: Aluminum-core light weight liquid-tight - GRAY 60°C	3/8" - 4"	
	ZHUA	16	Sealtite: Low smoke, Zero Halogen liquid-tight - BLACK 80°C	3/8" - 4"	
	Shieldtite®	17	Sealtite: Bronze-core High Shielding liquid-tight - GREY 105°C	3/8" - 4"	
	NWC	18	Sealtite: Radiation resistant metallic liquid-tight - BLACK 89°C	3/8" - 4"	
NM Liquid-tight	CNP	22	Sealtite: machine tool non-metallic liquid-tight - ORANGE 60°C	3/8" - 2"	 
	NMUA	24	Sealtite: Standard non-metallic liquid-tight - GREY 80°C	3/8" - 2-1/2"	 
	AC Whip Kits	24	Convenience AC Whip Kits	1/2" - 3/4"	 
	NMEF	25	Sealtite: Extra flexible non-metallic tubing - BLACK 80°C	3/8" - 2"	 
	ANA-QUICK	39	Ana-Quick: Nylon corrugated tubing - BLACK 120°C	1/4" - 2"	 
Non-jacketed	AlFlex-CSA	27	Aluminum non-jacketed flexible conduit	5/16" - 4"	
	RWA	28	Reduced Wall Aluminum non-jacketed flexible conduit	3/8" - 2"	
	RWS	29	Reduced Wall Steel non-jacketed flexible conduit	3/8" - 2"	
	DSL	30	Standard weight, galvanized steel , extra-flexible, OEM conduit	3/16" - 3/4"	
	DE-710 / DE-183	31	Heavy duty, galvanized steel , extra-flexible, OEM conduit	5/16" - 3/4"	
	SL	32	Standard weight, Stainless Steel , extra-flexible, OEM conduit	5/32" - 1/2"	
	UI-CAP	32	Heavy Duty, Stainless Steel , extra-flexible, OEM conduit	5/32" - 1/2"	
Firetech	FTS	35	Firetech Sleeve: High Temperature conduit insulation sleeving	1/4" - 5"	
	FTW	35	Firetech Wrap: High Temperature conduit insulation wrap	1" - 5"	
	FTT	35	Firetech Tape: High Temperature protective tape	1" & 1-1/2"	
	FSH	35	Firetech Sheet: High Temperature protective sheet	36", 40" & 60"	
	FTL	36	FireTech Lite: High Temperature insulation	1/2" - 4"	
Connectors	LT	20	Connectors: Metallic for metallic liquid-tight	3/8" - 2"	 
	SSLT	19	Connectors: Stainless for metallic liquid-tight	3/8" - 2"	
	STNM/SSNM	23	Connectors: Metallic for CNP (Type A) liquid-tight	3/8" - 2"	 
	NMSC/NMLT	26	Connectors: Non-metallic for non-metallic liquid-tight (Type B)	3/8" - 2"	 
	SSUI	33	Connectors: Stainless for Type DSL, SL and UI-CAP	3/8" - 1/2"	
	SSFT	36	Connectors: Stainless for Firetech Sleeve	3/8" - 1"	