



Sealtite Type HTUA: CSA/UL High Temp Flexible Conduit

Trade Size	Item ID	Std. Pkg. M (FT)	Inside Diameter Min	Outside Diameter		Bend Diameter	Weight Kg/m (lbs/cft)
				Min	Max		
3/8" (12)	37402	30 (100)	12.29 (0.484)	17.50 (0.690)	18.00 (0.710)	152 (6.0)	0.36 (24)
	37404	244 (800)					
1/2" (16)	37412	30 (100)	15.80 (0.622)	20.80 (0.820)	21.30 (0.840)	178 (7.0)	0.43 (29)
	37414	152 (500)					
3/4" (21)	37422	30 (100)	20.83 (0.820)	26.17 (1.030)	26.67 (1.050)	254 (10.0)	0.64 (43)
	37428	152 (100)					
1" (27)	37431	30 (100)	26.44 (1.041)	32.80 (1.290)	33.40 (1.315)	305 (12.0)	1.09 (73)
	37438	122 (400)					
1-1/4" (35)	37441	15 (50)	35.05 (1.380)	41.40 (1.630)	42.20 (1.660)	356 (14.0)	1.49 (100)
	37448	76 (250)					
1-1/2" (41)	37451	15 (50)	40.01 (1.575)	47.40 (1.865)	48.30 (1.900)	279 (11.0)	1.67 (112)
	37454	46 (150)					
2" (53)	37461	15 (50)	51.31 (2.020)	59.40 (2.340)	60.30 (2.375)	356 (14.0)	2.20 (148)
	37468	30 (100)					
2-1/2" (63)	37471	15 (100)	62.99 (2.480)	72.10 (2.840)	73.00 (2.875)	483 (19.0)	2.69 (181)
3" (78)	37481	7.6 (25)	77.98 (3.070)	87.90 (3.460)	88.90 (3.500)	762 (30.0)	3.79 (255)
4" (103)	37491	7.6 (25)	101.60 (4.000)	113.30 (4.460)	114.30 (4.500)	863 (34.0)	5.37 (361)

All dimensions in mm (inches)



Square Lock Design with copper wire 3/8" thru 1-1/4"



Interlocked Design 1-1/2" thru 4" (no ground wire)

Sealtite Type HTUA:



- Flexible metal core liquid-tight conduit
- Designed for applications where a higher temperature range with UL approval is required or desired.
- Suitable for use in hazardous locations per NEC: Class I, Zone 2 & Div. 2; Class II Div. 1 & 2; Class III Div. 1 & 2.
- Approved in US (per NEC) for direct burial applications up to 2".
- Also available in Black by special order.
- Uses standard liquid-tight connectors for easy installation.

For connectors for this conduit, see page 19-20
 For cutting instructions, see page 37
 For Chemical Resistance, see page 38

SPECIFICATIONS:

- Galvanized steel core with Liquid-tight PVC jacket
- Colour: Grey
- Temp. range: -46°C to +105°C (-51°F to +221°F)
CSA max: +75°C (+167°F)
- UV (sunlight) Resistant
- Corrosion Resistant
- CSA Approved: #LL15275
- UL Approved: # E18917

APPLICATIONS:

- Applications for high and low temperature where UL and CSA approvals are required.
- Steel and Petrochemical industries

Anamet Canada Inc.
 PO Box 240, 36 Wolfe St.
 Frankford, Ontario K0K 2C0

Phone: (613) 398-1313
 Fax: (613) 398-6262
 www.anametcanada.com
 E-mail: csr@anametcanada.com