

NON-METALLIC Series

ANAMET



Sealtite Type NMEF (Type B): Non-metallic Flexible Tubing




NMEF:



Trade Size	Item ID	Std. Pkg. M (FT)	Inside Diameter Min	Outside Diameter		Bend Diameter	Weight Kg/m (lbs/cft)
				Min	Max		
3/8" (12)	39802	30 (100)	12.29 (0.484)	17.53 (0.690)	18.03 (0.710)	102 (4.0)	0.13 (9)
1/2" (16)	39812	30 (100)	15.80 (0.622)	20.83 (0.820)	21.34 (0.840)	165 (6.5)	0.17 (11)
3/4" (21)	39822	30 (100)	20.83 (0.820)	26.16 (1.030)	26.67 (1.050)	216 (8.5)	0.20 (13)
1" (27)	39831	30 (100)	26.44 (1.041)	32.77 (1.290)	33.40 (1.315)	330 (13.0)	0.30 (20)
1-1/4" (35)	39841	30 (100)	35.05 (1.380)	41.40 (1.630)	42.16 (1.660)	406 (16.0)	0.33 (22)
1-1/2" (41)	39853	15 (50)	40.01 (1.575)	47.37 (1.865)	48.26 (1.900)	457 (18.0)	0.40 (27)
2" (53)	39861	15 (50)	51.31 (2.020)	59.44 (2.340)	60.33 (2.375)	564 (22.2)	0.67 (45)

All dimensions in mm (inches)

Co-extruded spiral with smooth inner wall



SPECIFICATIONS:

- Co-extruded PVC conduit.
- Extra Flexible
- Colour: Black
- Temp. range: -18°C to +80°C (0°F to +176°F)
Wet: +60°C (+140°F)
Oil: +70°C (+158°F)
- UV (sunlight) Resistant
- Oil Resistant

APPLICATIONS:

- OEM machine building.
- Industrial applications where tight bend radii are required.

Sealtite Type NMEF:



- **Non-metallic Type B liquid-tight tubing**
- **Designed for OEM and industrial applications**
- **Uses special non-metallic connectors for easy installation. Can also be used with standard liquid-tight connector.**
- **Available in custom cut lengths**

For connectors for this conduit, see page 26 (or 19-20)
For cutting instructions, see page 37
For Chemical Resistance, see page 38

Phone: (613) 398-1313
Fax: (613) 398-6262
www.anametcanada.com
E-mail: csr@anametcanada.com

Anamet Canada Inc.
PO Box 240, 36 Wolfe St.
Frankford, Ontario K0K 2C0