



Sealtite Type OR: Oil-Resistant Flexible Conduit

Trade Size	Item ID	Std. Pkg. M (FT)	Inside Diameter Min	Outside Diameter		Bend Diameter	Weight Kg/m (lbs/cft)
				Min	Max		
3/8" (12)	36602	30 (100)	12.32 (0.485)	17.53 (0.690)	18.03 (0.710)	101 (4.0)	0.31 (21)
1/2" (16)	36612	30 (100)	15.75 (0.620)	20.83 (0.820)	21.34 (0.840)	127 (5.0)	0.37 (25)
3/4" (21)	36622	30 (100)	20.70 (0.815)	26.16 (1.030)	26.67 (1.050)	152 (6.0)	0.58 (39)
1" (27)	36631	30 (100)	26.16 (1.030)	32.77 (1.290)	33.40 (1.315)	203 (8.0)	0.76 (51)
1-1/4" (35)	36641	15 (50)	34.80 (1.370)	41.53 (1.635)	42.16 (1.660)	229 (9.0)	0.98 (66)
1-1/2" (41)	36651	15 (50)	40.01 (1.575)	47.37 (1.865)	48.26 (1.900)	279 (11.0)	1.55 (104)
2" (53)	36661	15 (50)	51.31 (2.020)	59.44 (2.340)	60.33 (2.375)	355 (14.0)	2.02 (136)

All dimensions in mm (inches)



Square Lock Design with
cord packing 3/8" thru 1-1/4"



Interlocked Design 1-1/2"
thru 2"

Sealtite Type OR:

RoHS

- Flexible metal core liquid-tight conduit.
- Designed for applications that need superior resistance to petroleum, synthetic oils and chemical degradation.
- Also available in Black by special order.
- Uses standard liquid-tight connectors for easy installation.

For connectors for this conduit, see page 19-20
For cutting instructions, see page 37
For Chemical Resistance, see page 38

SPECIFICATIONS:

- Galvanized steel core with Liquid-tight PVC jacket
- Colour: Black
- Temp. range: -23°C to +105°C (-9°F to +221°F)
- UV (sunlight) Resistant
- Extra Oil Resistant
- Corrosion Resistant

APPLICATIONS:

- Extreme resistance to oil.
- Petrochemical and steel industries
- Applications where no approvals are required.