

Sealtite Type UA-CSA: UL & CSA Approved Flexible Conduit



Trade Size	Item ID	Std. Pkg. M (FT)	Inside Diameter Min	Outside Diameter		Bend Diameter	Weight Kg/M (lbs/cft)
				Min	Max		
3/8" (12)	34202	30 (100)	12.29 (0.484)	17.53 (0.690)	18.00 (0.710)	152 (6.0)	0.37 (25)
1/2" (16)	34212	30 (100)	15.80 (0.622)	20.88 (0.822)	21.30 (0.840)	178 (7.0)	0.43 (29)
	34213	305 (1000)					
3/4" (21)	34222	30 (100)	20.83 (0.820)	26.16 (1.030)	26.67 (1.050)	254 (10.0)	0.65 (44)
	34228	152 (500)					
1" (27)	34231	30 (100)	26.44 (1.041)	32.77 (1.290)	33.40 (1.315)	318 (12.0)	1.09 (73)
	34238	122 (400)					
1-1/4" (35)	34241	15 (50)	35.05 (1.380)	41.40 (1.630)	42.20 (1.660)	356 (14.0)	1.49 (100)
	34248	76 (250)					
1-1/2" (41)	34251	15 (100)	40.01 (1.575)	47.37 (1.865)	48.30 (1.900)	279 (11.0)	1.71 (112)
	34254	45 (150)					
2" (53)	34261	15 (50)	51.31 (2.020)	59.44 (2.340)	60.30 (2.375)	356 (14.0)	2.20 (148)
	34268	30 (100)					
2-1/2" (63)	34075	8 (27)	62.99 (2.480)	72.14 (2.840)	73.00 (2.875)	635 (19.0)	2.70 (182)
3" (78)	34085	8 (27)	77.98 (3.070)	87.88 (3.460)	88.90 (3.500)	762 (30.0)	3.79 (255)
4" (103)	34095	8 (27)	101.60 (4.000)	113.28 (4.460)	114.30 (4.500)	1016 (34.0)	5.39 (362)

All dimensions in mm (inches)

SPECIFICATIONS:

- Galvanized steel core with Liquid-tight PVC jacket
- Colour: Grey (2-1/2" - 4" Black)
- Temp. range: -20°C to +60°C (-4°F to +60°F)
- UV (sunlight) Resistant
- Corrosion Resistant
- CSA Approved: #LL15275
- UL Approved: #E18917

APPLICATIONS:

- Applications where CSA and UL approvals are required.

Square Lock Design with copper wire 3/8" thru 1-1/4"



Interlocked Design 1-1/2" thru 4" (no ground wire)



Sealtite Type UA-CSA:

RoHS



- Flexible metal core liquid-tight conduit
- Designed for applications at OEMs where UL & CSA approval is required or desirable.
- Approved in US (per NEC) for direct burial applications
- Suitable for use in hazardous locations per CEC & NEC: Class I, Zone 2 & Div. 2; Class II Div. 1 & 2; Class III Div. 1 & 2.
- Also available in Black by special order.
- Uses standard liquid-tight connectors for easy installation

For connectors for this conduit, see page 19-20
For cutting instructions, see page 37
For Chemical Resistance, see page 38